



MAGNETIC VEHICLE SIGNS CARE AND APPLICATION GUIDE

PREPARATION

Before attaching your magnetic vehicle signs;-

1. Please ensure that the area on the vehicle surface where the sign is to be attached is clean and dry. In addition apply a light wax prior to application.
2. The magnetic side of the vehicle signs must also be clean, dry and dust-free.

APPLICATION

Place one edge of the sign in 'contact' with the vehicle in the required position, then allow the magnetic sign to position itself in the correct position, feeding it from the original edge already in contact with the vehicle.

If the sign is not straight or not in the required position, peel the sign off and reposition again, repeating the above process.

Pay attention to all the edges of the sign as any slight lump will permit air or moisture under the sign and this could result in a detachment of the sign from the vehicle.

Also ensure that the whole surface of the sign has no bumps, wrinkles or air pockets so it fits snugly and smoothly against the vehicle.

MAINTENANCE

Remove the sign on a regular basis. Ideally this should be done every 2 to 3 days. In hot weather this **MUST** be done daily. Also in conditions of rain, sleet or snow the sign must be removed and wiped dry to prevent damage to the sign or vehicle.

Wipe dry both the surface of the vehicle and the magnetic side of the sign. This will prevent moisture from collecting, which could cause damage to the surface of the vehicle.

Wash the sign with warm soapy water, avoiding any cleaning fluids, solvents, acetone, petrol, chlorinated solvents or benzene. Remove any dirt or road-film before re-applying the sign.

STORAGE

1. When not in use – keep the magnetic sign flat
2. Store in a clean environment, preferably at room temperature.
3. Do not place heavy objects on the signs or leaned against them.
4. Ideally store the sign on a flat steel surface. This prevents the magnetic area attracting airborne dust particles.

NOTES

1. It is not advisable to apply to newly painted vehicle surfaces (new cars or newly re-painted). Allow 3 months after painting and then hand wax prior to application.
2. Signs should be positioned on the sides of vehicles. Do not place on the front of the vehicle, due to the air turbulence being at its maximum,
3. Do not place signs over engine compartments due to the heat from the engine.
4. Do not attach magnetic signs to body panels that contain any plastic filler as this will reduce their magnetic effectiveness.
5. Magnetic signs should be fitted to flat areas on the vehicle such as doors and side panels. They should be made to such a size that they fit nicely in the area and do not go over trim, sharp contours and panel edges.

MAGNETIZE 2 ADVERTISE LTD HAS NO CONTROL OVER HOW THE MAGNETIC SIGNS ARE CARED FOR, ALTERED, STORED, AND/OR USED, OR THE SURFACE TO WHICH THE SIGNS ARE APPLIED – THEREFORE THERE IS NO WARRANTY EXPRESSED OR IMPLIED AGAINST LOSS OF SIGN OR DAMAGE TO VEHICLE SURFACES.